

GLICERODAC 20

Composition

Glycerin polyethylene glycolether

Product data (specification)

Property	Value	Unit	Test method
Appearance at 20 °C	liquid, clear	-	visual
APHA colour number	≤ 50	mg Pt/l	DIN EN 1557
Hydroxyl value	174 - 192	mg KOH/g	DIN EN 13926
Water	≤ 0.25	% by mass	DIN EN 13267
pH value (5% in demin. water)	5.5 - 7.5	-	DIN EN 1262

General product description

Property	Value	Unit	Test method
Density at 25 °C	about 1.135	g/ml	DIN 51757
Flash point	> 125	°C	DIN 51376

Transport and packaging

Road tankcar

Storage

Stainless steel vessels (Steel No.: 1.4541 or 1.4571)

This information is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party patent rights. In particular, no guarantee of properties in the legal sense is implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Reference to trade names used by other companies is neither a recommendation, nor is it intended to suggest that similar products could not be used. All our business transactions shall exclusively be governed by our General Sales Conditions.

Sasol Germany GmbH